



RULLI CAMBRIDGE

Rulli Costipatori Trainati
Trailed Cambridge Roller



STANDARD:

- Apertura idraulica
- Dischi in ghisa 480
- Doppio snodo per autolivellamento (solo versione trainata)
- Barra luci posteriore (solo versione trainata)

STANDARD EQUIPMENT:

- Hydraulic opening
- Cast iron disc D480
- Double joint for sel leveling (only trailed version)
- Traffic signalling bar complete with linkage (trailed version only)



Rullo in trasporto
Roller on road transport



Rullo singolo
Single roller



Apertura idraulica
Hydraulic adjustment

Modello Model	Larghezza lavoro cm Working Width. cm	Largh. Trasporto cm Transport Width. cm	Peso Kg Weight Kg	
RULLI IN GHISA FISSO - CARRELLO IDRAULICO "CAMBRIDGE" FIX CAST IRON "CAMBRIDGE" ROLLER, HYDRAULIC CHARIOT				
RTH 290	300	150	1100	
RULLI IN GHISA TRAINATI IDRAULICI - 3 SEZIONI AUTOLIVELLANTI "CAMBRIDGE" TRAILED HYDRAULIC CAST IRON ROLLER- 3 SELF LEVELING SECTIONS "CAMBRIDGE"				
SN460 S C48	460	210	2050	
SN520 S C48	560	230	2290	
SN650 S C48	580	230	2750	
Accessori Optionals:			Peso Kg Weight Kg	
Omologazione stradale / Road homologation			-	

C.M.A. sas di Fornasari Ing. Mirco & C. - Via Guido Rossa 26/28 - 47016 PREDAPPIO (FC) - ITALY
Tel/Fax +39 0543.922255 - e-mail: info@cmamacchineagricole.com - www.cmamacchineagricole.com